

Index

- A**
- access auditing 19
 - access control 4
 - access control lists 25
 - applications access 15
 - applications run-time environment 17
 - current settings, determining 28
 - data access 9
 - environment 4
 - environment, customizing 20
 - environment, setting up programmatically 22
 - initialization of system 27
 - tags for new values 14
 - troubleshooting 27
 - access control definitions 21
 - access control environment 4
 - access control definitions, creating programmatically 21
 - ACL settings 24
 - ACL setup parameters 22
 - audit parms 23
 - control settings, querying 20
 - customizing 20
 - group access 7
 - initializing 4
 - multiple environments, setting up 20
 - overriding 21
 - passwords 21, 23, 24
 - preliminary requirements 4
 - setting up programmatically 22
 - user access 7
 - access control lists, deleting obsolete records 25
 - access control settings 20
 - access control tags, for new values 14
 - access to data
 - See* data access
 - ACL setup parameters 22
 - ACL setup values 24
 - administrator's password 21, 23, 24
 - applications
 - access to 15
 - access to functions 16
 - advanced applications development 43
 - class overrides 44
 - data access 9
 - drill level for 13
 - dropping columns from 10
 - metabase tuning 43
 - method overrides 44
 - run-time environment 17
 - subsetting data 11
 - audit parms 23
 - auditing access 19
- C**
- class overrides 44
 - columns, dropping from applications 10
 - Common Metadata Repository 39
 - converting SAS/EIS metabases 41
 - SASHELP repository 41
 - system repository manager files 40
 - system repository manager, location of 39
 - customizing access control environment 20
- D**
- data access 9
 - applications data access 9
 - drill levels for applications 13
 - dropping columns from applications 10
 - removing data from display 12
 - subsetting data for applications 11
 - data groups 31
 - registering 37
 - Distributed Multidimensional Metadata facility 30
 - drill levels 13
 - Drop tags 9
- E**
- EIS registrations 37
 - error messages 17
- F**
- functions access 16
- G**
- group access 7
 - groups, multiple per user 19
- H**
- help 1
 - Hide tags 9, 12
- K**
- Keep tags 9
- L**
- login windows
 - building 18
 - bypassing 18
 - customizing 18
 - login, troubleshooting 28
- M**
- MDP (Multidimensional Data Provider) 29
 - data requirements 30
 - setting up MDP metadata 30
 - without defining metadata 38
 - MDP metadata 30
 - data groups 31
 - EIS registrations 37
 - MDP without metadata 38
 - servers 34
 - messages 17
 - metabase tuning 43
 - metabases, converting 41
 - metadata
 - See also* Common Metadata Repository
 - See* MDP metadata
 - method overrides 44
 - Multidimensional Data Provider
 - See* MDP (Multidimensional Data Provider)
- P**
- passwords 21, 23, 24

R

- registrations 37
- removing data from reports 12
- reports, removing data from 12
- repositories
 - See Common Metadata Repository
- run-time environment 17
 - access auditing 19
 - assigning multiple groups to a user 19
 - login windows, bypassing 18
 - login windows, customizing 18
 - messages control 17

S

- SAS/EIS metabase facility
 - See Common Metadata Repository

- SAS/EIS metabases, converting 41
- SASHELP repository 41
- servers, MDP 34
- Show tags 12
- subsetting data 11
- subtables 33
- system repository manager
 - files for 40
 - location of 39

T

- tags
 - Drop tags 9
 - for new values 14
 - Hide tags 9, 12
 - Keep tags 9

- Show tags 12
- troubleshooting 27
 - determining current settings 28
 - initialization of access control system 27
 - login 28
 - user access 28

U

- user access 7
 - troubleshooting 28
- users, assigning to multiple groups 19

W

- warnings 17