



Length and Precision of Variables

Length and Precision of Variables under OS/2 389

Numeric Variables 389

Character Variables 390

Length and Precision of Variables under OS/2

For detailed information about how the SAS System stores representations of numeric and character data, see *SAS Language Reference: Concepts*. Data representation issues vary among different operating systems. The topics in this section discuss how data are represented in the SAS System under OS/2.

Numeric Variables

The default length of numeric variables in SAS data sets is 8 bytes. (You can control the length of SAS numeric variables with the LENGTH statement in the DATA step.) In the SAS System under OS/2, the OS/2 data type of numeric values that have a length of 8 is LONG REAL. The precision of this type of floating-point values is 16 decimal digits. For more information about the representation of the LONG REAL OS/2 data type, see Intel Corporation's *i486 Microprocessor Programmer's Reference Manual*. Table 19.1 on page 389 specifies the significant digits and largest integer values that can be stored in SAS numeric variables.

Table 19.1 Significant Digits and Largest Integer by Length for SAS Variables under OS/2

Length in Bytes	Largest Integer Represented Exactly	Exponential Notation
3	8,192	2^{13}
4	2,097,152	2^{21}
5	536,870,912	2^{29}
6	137,438,953,472	2^{37}

Length in Bytes	Largest Integer Represented Exactly	Exponential Notation
7	35,184,372,088,832	2^{45}
8	9,007,199,254,740,992	2^{53}

Suppose you know that a numeric variable always has values between 0 and 100, you can use a length of 3 to store the number and thus save space in your data set. The following is an example:

```
data mydata;
  length num 3;
  more data lines
run;
```

Note: *Dummy variables* (those whose only purpose is to hold 0 or 1) can be stored in a variable whose length is 3 bytes. Δ

CAUTION:

Use the 3-byte limit for only those variables whose values are small, preferably integers. If the value of a variable becomes large or has many significant digits, you may lose precision when saving the results of arithmetic calculations if the length of a variable is less than 8 bytes. Δ

Character Variables

In the SAS System under OS/2, character values are sorted using the ASCII collating sequence. As an alternative to the numeric dummy variables discussed previously, you can choose a character variable with a length of 1 byte to serve the same purpose.

The maximum number of variables in a single SAS data set under OS/2 is 32,767. In addition, an observation under OS/2 cannot be longer than 5M. Therefore, if you want your data set to contain 32,767 character variables, the longest each variable can be is 160 bytes.

However, a DATA step can reference more than 32,767 variables, if you write only 32,767 or fewer variables to the data set. For example, you could drop some variables with a DROP= data set option. Under OS/2, the maximum number of variables a DATA step can reference is 2,147,483,647.

The correct bibliographic citation for this manual is as follows: SAS Institute Inc., *SAS® Companion for the OS/2® Environment, Version 8*, Cary, NC: SAS Institute Inc., 1999. 448 pp.

SAS® Companion for the OS/2® Environment, Version 8

Copyright © 1999 by SAS Institute Inc., Cary, NC, USA.

ISBN 1-58025-521-3

All rights reserved. Produced in the United States of America. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, or otherwise, without the prior written permission of the publisher, SAS Institute Inc.

U.S. Government Restricted Rights Notice. Use, duplication, or disclosure of the software and related documentation by the U.S. government is subject to the Agreement with SAS Institute and the restrictions set forth in FAR 52.227-19 Commercial Computer Software-Restricted Rights (June 1987).

SAS Institute Inc., SAS Campus Drive, Cary, North Carolina 27513.

1st printing, October 1999

SAS® and all other SAS Institute Inc. product or service names are registered trademarks or trademarks of SAS Institute Inc. in the USA and other countries.® indicates USA registration.

IBM® and OS/2® are registered trademarks or trademarks of International Business Machines Corporation. ® indicates USA registration.

Other brand and product names are registered trademarks or trademarks of their respective companies.

The Institute is a private company devoted to the support and further development of its software and related services.